




N-Channel Enhancement Mode Power MOSFET

Description The G3404B uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications.		 Schematic diagram	
General Features • V_{DS} 30V • I_D (at $V_{GS} = 10V$) 5.6A • $R_{DS(ON)}$ (at $V_{GS} = 10V$) < 22mΩ • $R_{DS(ON)}$ (at $V_{GS} = 4.5V$) < 35mΩ • 100% Avalanche Tested • RoHS Compliant		 Marking and pin assignment	
Application • Power switch • DC/DC converters		 SOT-23	
Device	Package	Marking	Packaging
G3404B	SOT-23	G3404	3000pcs/Reel

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Continuous Drain Current	I_D	5.6	A
Pulsed Drain Current (note1)	I_{DM}	30	A
Gate-Source Voltage	V_{GS}	± 20	V
Power Dissipation	P_D	1.2	W
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 To 150	$^\circ\text{C}$

Thermal Resistance



Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	104	$^\circ\text{C/W}$

Specifications T _J = 25°C, unless otherwise noted						
Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	30	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30V, V _{GS} = 0V	--	--	1	uA
Gate-Source Leakage	I _{GSS}	V _{GS} = ±20V	--	--	±100	nA
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1	1.5	2	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 4.2A	--	18	22	mΩ
		V _{GS} = 4.5V, I _D = 4A	--	26	35	
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 15V, f = 1.0MHz	--	526	--	pF
Output Capacitance	C _{oss}		--	78	--	
Reverse Transfer Capacitance	C _{rss}		--	69	--	
Total Gate Charge	Q _g	V _{DS} = 15V, I _D = 5.6A, V _{GS} = 10V	--	12.2	--	nC
Gate-Source Charge	Q _{gs}		--	2.4	--	
Gate-Drain Charge	Q _{gd}		--	2.3	--	
Turn-on Delay Time	t _{d(on)}	V _{DS} = 15V, I _D = 5.6A, R _G = 3Ω	--	5	--	ns
Turn-on Rise Time	t _r		--	28	--	
Turn-off Delay Time	t _{d(off)}		--	13	--	
Turn-off Fall Time	t _f		--	22	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I _S	T _C = 25°C	--	--	5.6	A
Body Diode Voltage	V _{SD}	T _J = 25°C, I _{SD} = 1A, V _{GS} = 0V	--	--	1.2	V



Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. Identical low side and high side switch with identical R_G



Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Gate Charge




Figure 4. Drain Source On Resistance




Figure 5. Capacitance





Figure 6. On-Resistance vs. Junction Temperature



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. Source-Drain Diode Forward




Figure 8. Safe Operation Area






Figure 9. Normalized Maximum Transient Thermal Impedance



SOT-23 Package Information



Symbol	Dimensions in Millimeters	
	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°